




## Tenmat - Firefly 102-50 Ventilated Fire Barrier

SPEC ID: 55536

Tenmat Inc.
23 Copper Drive, Unit #3
Newport, DE 19804
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



## LISTING INFORMATION

The Firefly or FF 102-50 Fire Ventilated Fire Barrier Intumescent Seal is an ETL Recognized Component that is certified and approved to use in Intertek certified, NFPA 285-rated, ACM panel systems installed over mineral wool insulation. It is a rigid high expansion intumescent strip encased in aluminum foil. The FF102-50 is mechanically fastened to supporting members for panel systems (such as girts) using min. 2-in. long screws, in the center of the strip, spaced 8 in. oc (on center). The strip is positioned around the perimeter of the window approximately 6 in. from the center of the strip to the edge of the window opening.

## **FIRE RATINGS**

Test Description	Rating
NFPA 285	Meets Acceptance Critera

Attribute Value

Criteria NFPA 285 (2019)

CSI Code 07 81 23 Intumescent Fireproofing

Intertek Services Certification
Listed or Inspected LISTED

Listing Section ADDITIONAL COMPONENTS FOR WALL ASSEMBLIES

Listing Section Intumescent Fireproofing

Spec ID 55536